SIDUN 113 Self-Levelling Metal Joint Sealant

Catalogue SKU: SIDUN-113 | Version 1.0 | English | 21 November 2026

SIDUN 113 is a self-levelling sealant for narrow joints in compatible metal window and door profiles. Check the orientation and containment of the channel so the material can settle where the seal is needed.

Key features

Self-levelling placement • Intended for narrow metal profile seams • Small squeeze-pouch format

Typical applications

Contained seams in metal window profiles • Narrow channels in compatible door threshold profiles • Bench trials at level profile junctions

Substrates and compatibility

Use the actual metal finish and channel geometry in the evaluation. Account for plated, painted or anodised surfaces, channel outlets and adjoining materials that might contact any overflow.

Packaging

Matching photographs and 2025 and 2026 catalogue entries show a 150 mL squeeze pouch. Confirm the current pouch, dispense format and carton count for the order.

Application guidance

Prepare — clean the profile and position it so the selected section can hold the sealant. Apply — make a small trial fill and control outlets or drainage paths according to the assembly detail. Check — inspect bead coverage, leakage and cured adhesion on the trial piece.

Planning a trial

Share the profile section, gap dimensions, installed angle and whether it can be placed level during fabrication. Where the joint has an open or vertical run, confirm retention or select a format that suits that geometry.

Technical data and safety information

Confirm allowable gap dimensions, placement orientation, cure and coating compatibility for the selected version.

This sheet summarizes product identity and selection guidance. Request the applicable technical data sheet and safety data sheet for the selected model, packaging version and market. Confirm current packaging and availability before ordering.

Contact SIDUN · Technical Resources